


# ACT-800H UHF Digital Wideband Handheld Transmitter

## Features

- Aesthetically designed in champagne gold color metal housing features the most comfortable handheld size and presents ultra-low handling noise and a luxurious professional appearance.
- The unique metal grille of the microphone capsule module can be divided into the upper grille and the lower grille. The upper grille can be detached for cleaning; the lower grille is connected with the housing by an external thread. The robust metal grille protects the capsule against impact, rolling and pop noise, and ensures clarity of sound.
- The patented power switch module integrates the mute, set buttons, LCD and power switch lock hook for convenience to operate and prevents the power switch from accidental operation.
- In addition to the power switch and the mute button, functions such as input sensitivity, low frequency reduction, volume limit, power output and mute mode are also programmable.
- 3 switchable gain levels with input sensitivity preset to equal the sensitivity of the microphone capsule at 0 dB.
- The world's first ACT™ function provides precise and rapid frequency sync to the receiver.
- The patented battery compartment can be inserted with two AA-type batteries or one rechargeable Li-ion battery, charging via USB Type-C with the foolproof and safe charging circuit. The second-generation ACT-800H features charging contacts and can also be placed on an optional single-slot or dual-slot slip-in charger for charging.
- A color-coded channel identification ring is put on the end of the housing. A high efficiency wideband transmitting antenna and USB Type-C charging socket built in a patented antenna cover on the bottom of the housing.
- Pairs with all MIPRO's new interchangeable microphone modules featuring high dynamic range for loud singing without distortion. Also accepts some other brands' microphone modules with similar specifications.



## Specifications

Frequency Range	UHF 480 – 934 MHz (country dependent)
Bandwidth	72 MHz
Display	Backlit LCD
Encryption	256-bit
Mic. Capsule Modules	MU-90A condenser or MU-59A dynamic. Accepts some other brands' with similar specifications
AF Sensitivity	Preset at 0 dB (equal to capsule sensitivity) 3 switchable levels: 6 dB, 3 dB, 0 dB
RF Power Output	10 mW / 50 mW switchable (country dependent)
Spurious Emissions	< 4 nW
Battery Type	One 18500 Li-ion battery or two AA alkaline
Battery Charging	MP-800 / MP-820 charging station or USB Type-C
Dimensions	51 × 272 mm (Ø × L)
Weight	Approx. 331 g



### MIPRO Electronics Co., Ltd

Headquarters: 814 Beigang Road, Chiayi, 600079, Taiwan  
Tel: +886.5.238.0809 | Fax: +886.5.238.0803  
www.mipro.com.tw | mipro@mipro.com.tw

Specifications are subject to change without prior notice. CE024/02